

**FEATURED PRODUCTS**

**EPC102 Heating controller,...**

EPC102 is a communicative room heating controller (radiator, electric heater) with one triac output and one...



**mark320, mark220 DDC controllers, display**

Supply 10..35 V DC / 24 V AC. DIN rail mounting, dimensions 90 x 58 x 105 mm Ethernet, RS485, LCD display,...



**HT200 Touch screen operator unit**

Power 24 V DC, power supply not included Terminal with touch screen 7", 800x480, ARM, 256MB RAM,...



**markMX DDC controller, 88 I/O**

Supply 10..35 V DC / 24 V AC, dimensions 265 x 292 x 40 mm, 16 AI, 8 AO, 32 DI, 32 DO. Programming in...



**UI020BL Communicative room unit...**

The UI...BL room unit range is a family of universal communicative human-machine interface for control of HVAC...



**FCR011 Communicative fancoil...**

2 x DI (presence, window), 2 x DO triac 230 V AC for thermic valves (heating, cooling), 3 x DO relay for...



**R096 M-Bus / RS232 converter...**

R096 is a microprocessor-controlled M-Bus converter for energy and media meter readouts over RS232. The...



**ICIO205 DDC controller, 30 I/O,...**

Supply 10..35 V DC / 24 V AC, dimensions 217 x 115 x 40 mm, Ethernet, web, RS485, 8 AI, 6 AO, 8 DI, 8 DO....



**MW241 Small I/O module for LED...**

MW241 is a small I/O module featuring 2 DI and 2 DO (solid state relays). It is used for control of two...



**R560 Universal analogue input...**

The R560 is a microprocessor controlled, communicative module with 8 analogue inputs with variable measuring...

